



Leduro.com

CATALOGUE  
2018

# LED FILAMENT BULBS

E27 / E14



Model code	<b>70103</b>			<b>GLOBE LED FILAMENT</b>	
Power	<b>6.5 W</b>	Lamp base	<b>E27</b>	Ra	<b>&gt;80</b>
Light stream	<b>806 lm</b>	Beam angle	<b>360°</b>	Voltage	<b>220-240 V</b>
Color temperature	<b>2700 K</b>	Size	<b>D 95 mm / H 140 mm</b>	EAN code	<b>4750703021494</b>
		Life span	<b>25000 h</b>		



Model code	<b>70101</b>			<b>A60 LED FILAMENT</b>	
Power	<b>6.5 W</b>	Lamp base	<b>E27</b>	Ra	<b>&gt;80</b>
Light stream	<b>806 lm</b>	Beam angle	<b>360°</b>	Voltage	<b>220-240 V</b>
Color temperature	<b>2700 K</b>	Size	<b>D 60 mm / H 106 mm</b>	EAN code	<b>4750703022231</b>
		Life span	<b>25000 h</b>		



Model code	<b>70104</b>			<b>A60 LED FILAMENT</b>	
Power	<b>8 W</b>	Lamp base	<b>E27</b>	Ra	<b>&gt;80</b>
Light stream	<b>1055 lm</b>	Beam angle	<b>360°</b>	Voltage	<b>220-240 V</b>
Color temperature	<b>2700 K</b>	Size	<b>D 60 mm / H 106 mm</b>	EAN code	<b>4750703023504</b>
		Life span	<b>25000 h</b>		



Model code	<b>70202</b>			<b>G45 LED FILAMENT</b>	
Power	<b>4 W</b>	Lamp base	<b>E27</b>	Ra	<b>&gt;80</b>
Light stream	<b>400 lm</b>	Beam angle	<b>360°</b>	Voltage	<b>220-240 V</b>
Color temperature	<b>2700 K</b>	Size	<b>D 45 mm / H 73 mm</b>	EAN code	<b>4750703021487</b>
		Life span	<b>25000 h</b>		



Model code	<b>70201</b>			<b>G45 LED FILAMENT</b>	
Power	<b>4 W</b>	Lamp base	<b>E14</b>	Ra	<b>&gt;80</b>
Light stream	<b>400 lm</b>	Beam angle	<b>360°</b>	Voltage	<b>220-240 V</b>
Color temperature	<b>2700 K</b>	Size	<b>D 45 mm / H 78 mm</b>	EAN code	<b>4750703020541</b>
		Life span	<b>25000 h</b>		



Model code	<b>70301</b>			<b>C35 LED FILAMENT</b>	
Power	<b>4 W</b>	Lamp base	<b>E14</b>	Ra	<b>&gt;80</b>
Light stream	<b>400 lm</b>	Beam angle	<b>360°</b>	Voltage	<b>220-240 V</b>
Color temperature	<b>2700 K</b>	Size	<b>D 35 mm / H 100 mm</b>	EAN code	<b>4750703022248</b>
		Life span	<b>25000 h</b>		



Model code	<b>70303</b>			<b>C35 LED FILAMENT</b>	
Power	<b>5 W</b>	Lamp base	<b>E14</b>	Ra	<b>&gt;80</b>
Light stream	<b>550 lm</b>	Beam angle	<b>360°</b>	Voltage	<b>220-240 V</b>
Color temperature	<b>2700 K</b>	Size	<b>D 35 mm / H 100 mm</b>	EAN code	<b>4750703023498</b>
		Life span	<b>25000 h</b>		



Model code	<b>70302</b>			<b>C35 LED FILAMENT</b>	
Power	<b>4 W</b>	Lamp base	<b>E14</b>	Ra	<b>&gt;80</b>
Light stream	<b>400 lm</b>	Beam angle	<b>360°</b>	Voltage	<b>220-240 V</b>
Color temperature	<b>2700 K</b>	Size	<b>D 35 mm / H 115 mm</b>	EAN code	<b>4750703022347</b>
		Life span	<b>25000 h</b>		

# LED BULBS

E27 / E14



Model code	<b>21197</b>			<b>GLOBE LED BULB</b>	
Power	<b>15 W</b>	Lamp base	<b>E27</b>	Ra	<b>&gt;80</b>
Light stream	<b>1200 lm</b>	Beam angle	<b>360°</b>	Voltage	<b>220-240 V</b>
Color temperature	<b>2700 K</b>	Size	<b>D 120 mm / H 152 mm</b>	EAN code	<b>4750703012041</b>
		Life span	<b>25000 h</b>		



Model code	<b>21215</b>			<b>A65 LED BULB</b>	
Power	<b>15 W</b>	Lamp base	<b>E27</b>	Ra	<b>&gt;80</b>
Light stream	<b>1400 lm</b>	Beam angle	<b>220°</b>	Voltage	<b>220-240 V</b>
Color temperature	<b>3000 K</b>	Size	<b>D 65 mm / H 130 mm</b>	EAN code	<b>4750703022446</b>
		Life span	<b>25000 h</b>		



Model code	<b>21187</b>			<b>A65 LED BULB</b>	
Power	<b>12 W</b>	Lamp base	<b>E27</b>	Ra	<b>&gt;80</b>
Light stream	<b>1000 lm</b>	Beam angle	<b>360°</b>	Voltage	<b>220-240 V</b>
Color temperature	<b>2700 K</b>	Size	<b>D 65 mm / H 123 mm</b>	EAN code	<b>4750703995900</b>
		Life span	<b>25000 h</b>		



Model code	<b>21196</b>			<b>A60 LED BULB</b>	
Power	<b>9 W</b>	Lamp base	<b>E27</b>	Ra	<b>&gt;80</b>
Light stream	<b>800 lm</b>	Beam angle	<b>360°</b>	Voltage	<b>220-240 V</b>
Color temperature	<b>2700 K</b>	Size	<b>D 60 mm / H 110 mm</b>	EAN code	<b>4750703008570</b>
		Life span	<b>25000 h</b>		



Model code	<b>21184</b>			<b>A50 LED BULB</b>	
Power	<b>6 W</b>	Lamp base	<b>E27</b>	Ra	<b>&gt;80</b>
Light stream	<b>500 lm</b>	Beam angle	<b>360°</b>	Voltage	<b>220-240 V</b>
Color temperature	<b>2700 K</b>	Size	<b>D 55 mm / H 114 mm</b>	EAN code	<b>4750703995887</b>
		Life span	<b>25000 h</b>		



Model code	<b>21182</b>			<b>G45 LED BULB</b>	
Power	<b>5 W</b>	Lamp base	<b>E14</b>	Ra	<b>&gt;80</b>
Light stream	<b>400 lm</b>	Beam angle	<b>360°</b>	Voltage	<b>220-240 V</b>
Color temperature	<b>2700 K</b>	Size	<b>D 45 mm / H 80 mm</b>	EAN code	<b>4750703995863</b>
		Life span	<b>25000 h</b>		



Model code	<b>21183</b>			<b>G45 LED BULB</b>	
Power	<b>5 W</b>	Lamp base	<b>E27</b>	Ra	<b>&gt;80</b>
Light stream	<b>400 lm</b>	Beam angle	<b>360°</b>	Voltage	<b>220-240 V</b>
Color temperature	<b>2700 K</b>	Size	<b>D 45 mm / H 80 mm</b>	EAN code	<b>4750703995870</b>
		Life span	<b>25000 h</b>		



Model code	<b>21177</b>			<b>R63 LED BULB</b>
Power	<b>8 W</b>	Lamp base	<b>E27</b>	<b>&gt;80</b>
Light stream	<b>700 lm</b>	Beam angle	<b>180°</b>	<b>220-240 V</b>
Color temperature	<b>3000 K</b>	Size	<b>D 63 mm / H 105 mm</b>	<b>4750703995825</b>
		Life span	<b>25000 h</b>	
				<b>EAN code</b>



Model code	<b>21169</b>			<b>R50 LED BULB</b>
Power	<b>5 W</b>	Lamp base	<b>E14</b>	<b>&gt;80</b>
Light stream	<b>400 lm</b>	Beam angle	<b>360°</b>	<b>220-240 V</b>
Color temperature	<b>3000 K</b>	Size	<b>D 50 mm / H 86 mm</b>	<b>4750703995627</b>
		Life span	<b>25000 h</b>	
				<b>EAN code</b>



Model code	<b>21188</b>			<b>C35 LED BULB</b>
Power	<b>5 W</b>	Lamp base	<b>E14</b>	<b>&gt;80</b>
Light stream	<b>400 lm</b>	Beam angle	<b>180°</b>	<b>220-240 V</b>
Color temperature	<b>2700 K</b>	Size	<b>D 35 mm / H 99 mm</b>	<b>4750703995917</b>
		Life span	<b>25000 h</b>	
				<b>EAN code</b>



Model code	<b>21130</b>			<b>C35 LED BULB</b>
Power	<b>3 W</b>	Lamp base	<b>E14</b>	<b>&gt;80</b>
Light stream	<b>200 lm</b>	Beam angle	<b>180°</b>	<b>220-240 V</b>
Color temperature	<b>2700 K</b>	Size	<b>D 35 mm / H 99 mm</b>	<b>4750703022255</b>
		Life span	<b>25000 h</b>	
				<b>EAN code</b>

# LED BULBS

**GU10 /  
GU5.3 MR16 / AR111**



Model code	<b>21200</b>			<b>PAR16 LED BULB</b>
Power	<b>7.5 W</b>	Lamp base	<b>GU10</b>	<b>&gt;80</b>
Light stream	<b>600 lm</b>	Beam angle	<b>60°</b>	<b>220-240 V</b>
Color temperature	<b>3000 K</b>	Size	<b>D 50 mm / H 50 mm</b>	<b>4750703023481</b>
		Life span	<b>25000 h</b>	
				<b>EAN code</b>



Model code	<b>21194</b>			<b>PAR16 LED BULB</b>
Power	<b>7 W</b>	Lamp base	<b>GU10</b>	<b>&gt;80</b>
Light stream	<b>600 lm DIM</b>	Beam angle	<b>60°</b>	<b>220-240 V</b>
Color temperature	<b>3000 K</b>	Size	<b>D 50 mm / H 50 mm</b>	<b>4750703023320</b>
		Life span	<b>25000 h</b>	
				<b>EAN code</b>



Model code	<b>21192</b>			<b>PAR16 LED BULB</b>
Power	<b>5 W</b>	Lamp base	<b>GU10</b>	<b>&gt;80</b>
Light stream	<b>400 lm</b>	Beam angle	<b>100°</b>	<b>220-240 V</b>
Color temperature	<b>3000 K</b>	Size	<b>D 50 mm / H 50 mm</b>	<b>4750703995955</b>
		Life span	<b>25000 h</b>	
				<b>EAN code</b>



Model code	<b>21174</b>			<b>PAR16 LED BULB</b>
Power	<b>4 W</b>	Lamp base	<b>GU10</b>	Ra
Light stream	<b>300 lm</b>	Beam angle	<b>90°</b>	<b>&gt;80</b>
Color temperature	<b>3000 K</b>	Size	<b>D 50 mm / H 50 mm</b>	Voltage
		Life span	<b>25000 h</b>	<b>220-240 V</b>
				EAN code
				<b>4750703995689</b>



Model code	<b>21170</b>			<b>PAR16 LED BULB</b>
Power	<b>3 W</b>	Lamp base	<b>GU10</b>	Ra
Light stream	<b>250 lm</b>	Beam angle	<b>90°</b>	<b>&gt;80</b>
Color temperature	<b>3000 K</b>	Size	<b>D 50 mm / H 50 mm</b>	Voltage
		Life span	<b>25000 h</b>	<b>220-240 V</b>
				EAN code
				<b>4750703995634</b>



Model code	<b>21179</b>			<b>MR16 LED BULB</b>
Power	<b>3 W</b>	Lamp base	<b>GU5.3</b>	Ra
Light stream	<b>250 lm</b>	Beam angle	<b>100°</b>	<b>&gt;80</b>
Color temperature	<b>3000 K</b>	Size	<b>D 50 mm / H 38 mm</b>	Voltage
		Life span	<b>25000 h</b>	<b>AC/DC 12 V</b>
				EAN code
				<b>4750703995849</b>



Model code	<b>21191</b>			<b>MR16 LED BULB</b>
Power	<b>5 W</b>	Lamp base	<b>GU5.3</b>	Ra
Light stream	<b>400 lm</b>	Beam angle	<b>100°</b>	<b>&gt;80</b>
Color temperature	<b>3000 K</b>	Size	<b>D 50 mm / H 38 mm</b>	Voltage
		Life span	<b>25000 h</b>	<b>AC/DC 12 V</b>
				EAN code
				<b>4750703995924</b>



Model code	<b>21096</b>			<b>AR111 LED BULB</b>
Power	<b>14 W</b>	Lamp base	<b>GU10</b>	Ra
Light stream	<b>900 lm</b>	Beam angle	<b>45°</b>	<b>&gt;80</b>
Color temperature	<b>3000 K</b>	Size	<b>D 111 mm / H 62 mm</b>	Voltage
		Life span	<b>25000 h</b>	<b>220-240 V</b>
				EAN code
				<b>4750703023337</b>



Model code	<b>21094</b>			<b>AR111 LED BULB</b>
Power	<b>14 W</b>	Lamp base	<b>G53</b>	Ra
Light stream	<b>1000 lm</b>	Beam angle	<b>45°</b>	<b>&gt;80</b>
Color temperature	<b>3000 K</b>	Size	<b>D 111 mm / H 62 mm</b>	Voltage
		Life span	<b>25000 h</b>	<b>AC/DC 12 V</b>
				EAN code
				<b>4750703995528</b>

# LED BULBS

G9 / G4 / Gx53 / R7S



Model code	<b>21054</b>			<b>LED BULB</b>
Power	<b>5.5 W</b>	Lamp base	<b>G9</b>	Ra
Light stream	<b>500 lm</b>	Beam angle	<b>360°</b>	<b>&gt;80</b>
Color temperature	<b>2700 K</b>	Size	<b>D 16 mm / H 62 mm</b>	Voltage
		Life span	<b>25000 h</b>	<b>220-240 V</b>
				EAN code
				<b>4750703023290</b>



Model code	<b>21053</b>			<b>LED BULB</b>
Power	<b>3.5 W</b>	Lamp base	<b>G9</b>	<b>&gt;80</b>
Light stream	<b>350 lm</b>	Beam angle	<b>360°</b>	<b>220-240 V</b>
Color temperature	<b>2700 K</b>	Size	<b>D 16 mm / H 50 mm</b>	<b>4750703023283</b>
		Life span	<b>25000 h</b>	



Model code	<b>21057</b>			<b>LED BULB</b>
Power	<b>3.5 W</b>	Lamp base	<b>G9</b>	<b>&gt;80</b>
Light stream	<b>350 lm</b>	Beam angle	<b>360°</b>	<b>220-240 V</b>
Color temperature	<b>2700 K</b>	Size	<b>D 16 mm / H 50 mm</b>	<b>4750703023474</b>
		Life span	<b>25000 h</b>	<b>Dimmable LED</b>



Model code	<b>21052</b>			<b>LED BULB</b>
Power	<b>2.5 W</b>	Lamp base	<b>G9</b>	<b>&gt;80</b>
Light stream	<b>230 lm</b>	Beam angle	<b>300°</b>	<b>220-240 V</b>
Color temperature	<b>2700 K</b>	Size	<b>D 16 mm / H 52 mm</b>	<b>4750703019422</b>
		Life span	<b>25000 h</b>	



Model code	<b>21056</b>			<b>LED BULB</b>
Power	<b>2.5 W</b>	Lamp base	<b>G4</b>	<b>&gt;80</b>
Light stream	<b>200 lm</b>	Beam angle	<b>300°</b>	<b>AC/DC 12 V</b>
Color temperature	<b>2700 K</b>	Size	<b>D 13 mm / H 37 mm</b>	<b>4750703023306</b>
		Life span	<b>25000 h</b>	<b>Dimmable LED</b>



Model code	<b>21051</b>			<b>LED BULB</b>
Power	<b>1.5 W</b>	Lamp base	<b>G4</b>	<b>&gt;80</b>
Light stream	<b>100 lm</b>	Beam angle	<b>300°</b>	<b>AC/DC 12 V</b>
Color temperature	<b>2700 K</b>	Size	<b>D 12 mm / H 37 mm</b>	<b>4750703019415</b>
		Life span	<b>25000 h</b>	



Model code	<b>21199</b>			<b>LED BULB</b>
Power	<b>7 W</b>	Lamp base	<b>GX53</b>	<b>&gt;80</b>
Light stream	<b>600 lm</b>	Beam angle	<b>100°</b>	<b>220-240 V</b>
Color temperature	<b>3000 K</b>	Size	<b>D 75 mm / H 28 mm</b>	<b>4750703019040</b>
		Life span	<b>25000 h</b>	



Model code	<b>10055</b>			<b>LED BULB</b>
Power	<b>10 W</b>	Lamp base	<b>R7S</b>	<b>&gt;80</b>
Light stream	<b>1000 lm</b>	Beam angle	<b>360°</b>	<b>220-240 V</b>
Color temperature	<b>3000 K</b>	Size	<b>D 22 mm / H 118 mm</b>	<b>4750703013895</b>
		Life span	<b>25000 h</b>	



Model code	<b>10053</b>			<b>LED BULB</b>
Power	<b>5 W</b>	Lamp base	<b>R7S</b>	<b>&gt;80</b>
Light stream	<b>480 lm</b>	Beam angle	<b>360°</b>	<b>220-240 V</b>
Color temperature	<b>3000 K</b>	Size	<b>D 18 mm / H 78 mm</b>	<b>4750703023313</b>
		Life span	<b>25000 h</b>	

# LED LUMINARIES



IP44 / IP20



Model code	<b>95200</b>			<b>NOVA12 LED</b>
Power	12 W	Degree of protection	<b>IP44</b>	Ra
Light stream	<b>800 lm</b>	Beam angle	<b>120°</b>	<b>&gt;80</b>
Color temperature	<b>4000 K</b>	Size	<b>D 260 mm / H 95 mm</b>	Voltage
UGR	<b>&lt;19</b>	Life span	<b>25000 h</b>	<b>220-240 V</b>
				EAN code
				<b>4750703023382</b>



Model code	<b>95210</b>			<b>NOVA24 LED</b>
Power	24 W	Degree of protection	<b>IP44</b>	Ra
Light stream	<b>1700 lm</b>	Beam angle	<b>120°</b>	<b>&gt;80</b>
Color temperature	<b>4000 K</b>	Size	<b>D 385 mm / H 100 mm</b>	Voltage
UGR	<b>&lt;19</b>	Life span	<b>25000 h</b>	<b>220-240 V</b>
				EAN code
				<b>4750703023412</b>



Model code	<b>95220</b>			<b>NOVA SENSOR</b>
Power	12 W	Degree of protection	<b>IP20</b>	Ra
Light stream	<b>800 lm</b>	Beam angle	<b>120°</b>	<b>&gt;80</b>
Color temperature	<b>4000 K</b>	Size	<b>D 260 mm / H 95 mm</b>	Voltage
UGR	<b>&lt;19</b>	Life span	<b>25000 h</b>	<b>220-240 V</b>
				EAN code
				<b>4750703023429</b>



Model code	<b>95230</b>			<b>SUPER NOVA 36</b>
Power	36 W	Degree of protection	<b>IP20</b>	Ra
Light stream	<b>2600 lm</b>	Beam angle	<b>120°</b>	<b>&gt;80</b>
Color temperature	<b>4000 K</b>	Size	<b>D 480 mm / H 60 mm</b>	Voltage
UGR	<b>&lt;19</b>	Life span	<b>25000 h</b>	<b>220-240 V</b>
				EAN code
				<b>4750703023436</b>



Model code	<b>95240</b>			<b>SUPER NOVA 60</b>
Power	60 W	Degree of protection	<b>IP20</b>	Ra
Light stream	<b>5000 lm</b>	Beam angle	<b>120°</b>	<b>&gt;80</b>
Color temperature	<b>4000 K</b>	Size	<b>D 550 mm / H 65 mm</b>	Voltage
UGR	<b>&lt;19</b>	Life span	<b>25000 h</b>	<b>220-240 V</b>
				EAN code
				<b>4750703023443</b>



Model code	<b>31510</b>			<b>LINE10</b>
Power	10 W	Degree of protection	<b>IP20</b>	Ra
Light stream	<b>900 lm</b>	Beam angle	<b>180°</b>	<b>&gt;80</b>
Color temperature	<b>3000 K</b>	Size	<b>D 600 mm / H 16 mm</b>	Voltage
		Life span	<b>25000 h</b>	<b>220-240 V</b>
				EAN code
				<b>4750703022286</b>



Model code	<b>31520</b>			<b>LINE20</b>
Power	20 W	Degree of protection	<b>IP20</b>	Ra
Light stream	<b>1800 lm</b>	Beam angle	<b>180°</b>	<b>&gt;80</b>
Color temperature	<b>3000 K</b>	Size	<b>D 1200 mm / H 16 mm</b>	Voltage
		Life span	<b>25000 h</b>	<b>220-240 V</b>
				EAN code
				<b>4750703022293</b>

# RECESSED DOWNLIGHT



IP20



Model code	<b>80001</b>				<b>SQUARE</b>
Base included	<b>GU10</b>	Degree of protection	<b>IP20</b>	EAN code	<b>4750703022361</b>
		Size	<b>82x82 mm</b>	$\emptyset$	<b>70 mm</b>



Model code	<b>80002</b>				<b>SQUARE</b>
Base included	<b>GU10</b>	Degree of protection	<b>IP20</b>	EAN code	<b>4750703022385</b>
		Size	<b>92x92 mm</b>	$\emptyset$	<b>80 mm</b>



Model code	<b>80003</b>				<b>RING</b>
Base included	<b>GU10</b>	Degree of protection	<b>IP20</b>	EAN code	<b>4750703022354</b>
		Size	<b>D 82 mm</b>	$\emptyset$	<b>70 mm</b>



Model code	<b>80004</b>				<b>RING</b>
Base included	<b>GU10</b>	Degree of protection	<b>IP20</b>	EAN code	<b>4750703022378</b>
		Size	<b>D 92 mm</b>	$\emptyset$	<b>80 mm</b>



Model code	<b>80005</b>				<b>SQUARE 2</b>
Base included	<b>2 x GU10</b>	Degree of protection	<b>IP20</b>	EAN code	<b>4750703022392</b>
		Size	<b>92x175 mm</b>	$\emptyset$	<b>80x165 mm</b>



Model code	<b>80006</b>				<b>SQUARE 3</b>
Base included	<b>3 x GU10</b>	Degree of protection	<b>IP20</b>	EAN code	<b>4750703022408</b>
		Size	<b>92x260 mm</b>	$\emptyset$	<b>80x245 mm</b>



Model code	<b>80007</b>				<b>UNO</b>
Base included	<b>GU10</b>	Degree of protection	<b>IP20</b>	EAN code	<b>4750703022450</b>
		Size	<b>D 80 mm / H 21 mm</b>	$\emptyset$	<b>70 mm</b>





Model code	<b>80008</b>				UNO
Base included	<b>GU10</b>	Degree of protection	<b>IP20</b>	EAN code	<b>4750703023467</b>
		Size	<b>D 80 mm / H 21 mm</b>		<b>70 mm</b>

# LED FLOODLIGHTS

IP65



Model code	<b>46550</b>				<b>PRO 50</b>
Power	<b>50 W</b>	Degree of protection	<b>IP65</b>	Ra	<b>&gt;80</b>
Light stream	<b>5000 lm</b>	Beam angle	<b>100°</b>	Voltage	<b>85-265 V</b>
Color temperature	<b>4000 K</b>	Size	<b>235x200x67 mm</b>	EAN code	<b>4750703015301</b>
		Life span	<b>25000 h</b>		



Model code	<b>46530</b>				<b>PRO 30</b>
Power	<b>30 W</b>	Degree of protection	<b>IP65</b>	Ra	<b>&gt;80</b>
Light stream	<b>3000 lm</b>	Beam angle	<b>100°</b>	Voltage	<b>85-265 V</b>
Color temperature	<b>4000 K</b>	Size	<b>192x172x60 mm</b>	EAN code	<b>4750703015295</b>
		Life span	<b>25000 h</b>		



Model code	<b>36530</b>				<b>EKO 30</b>
Power	<b>30 W</b>	Degree of protection	<b>IP65</b>	Ra	<b>&gt;80</b>
Light stream	<b>2700 lm</b>	Beam angle	<b>100°</b>	Voltage	<b>85-265 V</b>
Color temperature	<b>4000 K</b>	Size	<b>225x185x55 mm</b>	EAN code	<b>4750703022470</b>
		Life span	<b>25000 h</b>		



Model code	<b>36520</b>				<b>EKO 20</b>
Power	<b>20 W</b>	Degree of protection	<b>IP65</b>	Ra	<b>&gt;80</b>
Light stream	<b>1800 lm</b>	Beam angle	<b>100°</b>	Voltage	<b>85-265 V</b>
Color temperature	<b>4000 K</b>	Size	<b>180x140x45 mm</b>	EAN code	<b>4750703022460</b>
		Life span	<b>25000 h</b>		

# LED PANELS



IP20

We produce panels only from high quality materials. Aluminum frame and PMMA diffuser. We offer warranty up to 5 years.



Model code	<b>93600</b>	<b>VISOLUX LED PANEL 60x60</b>			
Power	<b>42 W</b>	Degree of protection	<b>IP20</b>	Ra	<b>&gt;80</b>
Light stream	<b>3600 lm</b>	Beam angle	<b>120°</b>	Voltage	<b>220-240 V</b>
Color temperature	<b>4000 K</b>	Size	<b>595x595x10 mm</b>	EAN code	<b>4750703022491</b>
UGR	<b>&lt;19</b>	Life span	<b>25000 h</b>	Power supply	<b>+</b>



Model code	<b>93601</b>	<b>VISOLUX LED PANEL 60x60</b>			
Power	<b>42 W</b>	Degree of protection	<b>IP20</b>	Ra	<b>&gt;80</b>
Light stream	<b>3600 lm</b>	Beam angle	<b>120°</b>	Voltage	<b>220-240 V</b>
Color temperature	<b>3000 K</b>	Size	<b>595x595x10 mm</b>	EAN code	<b>4750703023269</b>
UGR	<b>&lt;19</b>	Life span	<b>25000 h</b>	Power supply	<b>+</b>



Model code	<b>94200</b>	<b>VISOLUX LED PANEL 60x60</b>			
Power	<b>42 W</b>	Degree of protection	<b>IP20</b>	Ra	<b>&gt;80</b>
Light stream	<b>4200 lm</b>	Beam angle	<b>120°</b>	Voltage	<b>220-240 V</b>
Color temperature	<b>4000 K</b>	Size	<b>595x595x10 mm</b>	EAN code	<b>4750703023276</b>
UGR	<b>&lt;19</b>	Life span	<b>25000 h</b>	Power supply	<b>+</b>

# LED PANEL ACCESSORIES



Model code	<b>90000</b>	<b>LED PANEL FIXTURE KIT 3</b>	
<b>LED panel fixture kit</b> <b>595x595 h1m</b>		EAN code	<b>4750703023528</b>



Model code	<b>90001</b>	<b>LED PANEL FIXTURE KIT 1</b>	
<b>LED panel fixture</b> <b>(for regips)</b>		EAN code	<b>4750703023535</b>



Model code	<b>90002</b>	<b>LED PANEL FRAME KIT 5</b>	
<b>LED panel frame white</b> <b>600x600</b>		EAN code	<b>4750703023511</b>

# LED PANELS



## IP20



Model code	<b>94210</b>			<b>ULTRA SLIM</b>
Power	12 W	Degree of protection	IP20	Ra
Light stream	720 lm	Beam angle	120°	>80
Color temperature	4000 K	Size	D 170 mm / H 20 mm	Voltage
UGR	<19	Life span	25000 h	220-240 V
		 ∅	150 mm	EAN code
				4750703023344
				Power supply
				+




Model code	<b>94220</b>			<b>ULTRA SLIM</b>
Power	12 W	Degree of protection	IP20	Ra
Light stream	720 lm	Beam angle	120°	>80
Color temperature	3000 K	Size	D 170 mm / H 20 mm	Voltage
UGR	<19	Life span	25000 h	220-240 V
		 ∅	150 mm	EAN code
				4750703023368
				Power supply
				+



Model code	<b>94230</b>			<b>ULTRA SLIM</b>
Power	18 W	Degree of protection	IP20	Ra
Light stream	1200 lm	Beam angle	120°	>80
Color temperature	4000 K	Size	D 225 mm / H 20 mm	Voltage
UGR	<19	Life span	25000 h	220-240 V
		 ∅	205 mm	EAN code
				4750703023351
				Power supply
				+



Model code	<b>94240</b>			<b>ULTRA SLIM</b>
Power	18 W	Degree of protection	IP20	Ra
Light stream	1200 lm	Beam angle	120°	>80
Color temperature	3000 K	Size	D 225 mm / H 20 mm	Voltage
UGR	<19	Life span	25000 h	220-240 V
		 ∅	205 mm	EAN code
				4750703023375
				Power supply
				+



Model code	<b>94250</b>			<b>ULTRA SLIM</b>
Power	24 W	Degree of protection	IP20	Ra
Light stream	1700 lm	Beam angle	120°	>80
Color temperature	4000 K	Size	D 300 mm / H 20 mm	Voltage
UGR	<19	Life span	25000 h	220-240 V
		 ∅	280 mm	EAN code
				4750703023399
				Power supply
				+



Model code	<b>94260</b>			<b>ULTRA SLIM</b>
Power	24 W	Degree of protection	IP20	Ra
Light stream	1700 lm	Beam angle	120°	>80
Color temperature	3000 K	Size	D 300 mm / H 20 mm	Voltage
UGR	<19	Life span	25000 h	220-240 V
		 ∅	280 mm	EAN code
				4750703023405
				Power supply
				+

Leduro.com



LIGHTINGBRANDS

**Lighting Brands Ltd** (Head Office)

4 Manor Farm Grove  
Bishopstoke  
SO50 6LY

**United Kingdom**

+44 2380317286  
export@lighting-brands.com



LIGHTINGBRANDS

**Poland**

poland@lighting-brands.com



LIGHTINGBRANDS

**Romania**

romania@lighting-brands.com



LIGHTINGBRANDS

**UAE**

uae@lighting-brands.com



LIGHTINGBRANDS

**Hungary**

hungary@lighting-brands.com



LIGHTINGBRANDS

**Ukraine**

ukraine@lighting-brands.com



LIGHTINGBRANDS

**Belarus**

belarus@lighting-brands.com



LIGHTINGBRANDS

**Czech Republic**

czech@lighting-brands.com



LIGHTINGBRANDS

**Greece**

greece@lighting-brands.com